

GEBERIT SIGMA01 ACTUATORS

For Sigma Concealed Tanks, 2x6 and 2x4 Installations

SPECIFICATIONS

Actuators for concealed tank and carrier system. Actuator flush plates and push buttons shall be molded plastic and plated to guard against scratches. All components shall be compliant with applicable codes and product standards.

FEATURES

- Designed to maintain appearance push after push
- Moving parts are accessible behind actuator flush plate
- Made of molded plastic and plated
- Available in a variety of unique combinations of finish/color
- Incorporates water saving possibilities when used with Geberit dual-flush tanks
 1.6 GPF (6 LPF) and 0.8 GPF (3 LPF) or
 1.28 GPF (4.8 LPF) and 0.8 GPF (3 LPF)
- Includes mounting frame and hardware


WARRANTY

• One-year limited warranty



DIMENSIONS

Sigma01 Dual-Flush



Products marked with comply with the American Disabilities Act (ADA) when installed per the requirements of the latest ADA Accessibility Guidelines (ADAAG) and/or ICC/ANSI A117.1.



| ARCHITECT/ENGINEER APPROVAL Job Name: | |
|--|-----------|
| | |
| Date: | Quantity: |
| Model Specifi | ed: |
| Variations Spe | ecified: |
| | |
| Customer/Wh | olesaler: |
| | |
| Contractor: | |
| Architect: | |
| | |
| | |



Geberit 2100 S. Clearwater Drive Des Plaines, IL 60018 USA

P 847-803-7777 F 847-849-1845

www.geberit.us