

GEBERIT TYPE 70 REMOTE BUTTON ACTUATORS

For Sigma and Omega Concealed Tanks, 2x6 and 2x4 installations

SPECIFICATIONS

Actuators for concealed tank and carrier system. Remote push buttons shall be glass, stainless steel. All components shall be compliant with applicable codes and product standards.

FEATURES



- Designed to maintain appearance push after push
- Incorporates water saving possibilities when used with Geberit dual-flush tanks 1.6 GPF (6 LPF) and 0.8 GPF (3 LPF) or 1.28 GPF (4.8 LPF) and 0.8 GPF (3 LPF)
- Available in a variety of colors and materials
- All can be placed anywhere within a 5.5 ft. radius of the concealed tank
- For furniture as well as solid and drywall construction
- Pneumatic remote flush
- Moving parts are accessible behind cover plate
- Accessible (ADA) versions available
- Includes mounting hardware

WARRANTY

- One-year limited warranty


DIMENSIONS

Type 70 Dual-Flush




Sigma Cover Plate for use with flush buttons

Standard:




Customizable for surface-even install:




Omega Cover Plate for use with flush buttons

Standard:



Customizable for surface-even install:



*NOTE: Customizable surface-even cover plate accepts typical wallcovering materials to disguise the service opening. Minimum finished wall is $\geq 3/4$ " (1.8 cm) plus cover thickness up to a maximum of 2" (5 cm) total.

Products marked with comply with the American Disabilities Act (ADA) when installed per the requirements of the latest ADA Accessibility Guidelines (ADAAG) and/or ICC/ANSI A117.1.



Geberit
2100 S. Clearwater Drive
Des Plaines, IL 60018
USA

P 847-803-7777
F 847-849-1845

www.geberit.us







ARCHITECT/ENGINEER APPROVAL	
Job Name:	_____
Date:	_____
Model Specified:	_____
Variations Specified:	_____
Customer/Wholesaler:	_____
Contractor:	_____
Architect:	_____


GEBERIT TYPE 70 REMOTE BUTTON ACTUATORS

For Sigma and Omega Concealed Tanks, 2x6 and 2x4 installations


Dual-Flush Remote Button Actuators for Concealed Installations

Style	Material	Finish	Installation System		
			Sigma 2x6	Sigma 2x4	Omega 2x6
Type 70 	Stainless	Brushed Stainless Steel 	115.630.FW.1	115.635.FW.1	115.084.FW.1
		Glass	White Glass 	115.630.SI.1	115.635.SI.1
		Black Glass 	115.630.SJ.1	115.635.SJ.1	115.084.SJ.1
		Lava Glass NEW!	115.630.JK.1	115.635.JK.1	115.084.JK.1
		Grey Sand Glass NEW!	115.630.JL.1	115.635.JL.1	115.084.JL.1

Cover Plates for use with flush buttons

Style	Material	Finish	Installation System			
			Sigma 2x6	Sigma 2x4	Omega 2x6	
	Glass	White	115.766.SI.1	115.766.SI.1	115.082.SI.1	
		Stainless	Brushed Stainless Steel	115.764.FW.1	115.764.FW.1	—
			Vandal Resistant	115.766.00.1	115.766.00.1	115.082.00.1
	Plastic	Alpine White	115.768.11.1	115.768.11.1	—	
		Polished Chrome	115.768.21.1	115.768.21.1	—	
		Matte Chrome	115.768.46.1	115.768.46.1	—	

Surface Even Cover Plates for use with flush buttons†

	Plastic	Customizable + rough-in kit	115.696.00.1 + 243.168.00.1	115.696.00.1	115.087.00.1
		Customizable with frame + rough-in kit	115.697.00.1 + 243.168.00.1	115.697.00.1	115.088.00.1

† For tile, stone or other hard surface walls only!

Geberit
2100 S. Clearwater Drive
Des Plaines, IL 60018
USA

P 847-803-7777
F 847-849-1845

www.geberit.us