

# **GEBERIT OMEGA60 ACTUATORS**

### For Omega Concealed Tanks, 2x6 Installations

#### **SPECIFICATIONS**

Actuators for concealed tank and carrier system. Actuator flush plates and push buttons shall be glass, zinc die-cast, and plated to guard against scratches. For tile, stone or other hard surfaced walls only. All components shall be compliant with applicable codes and product standards.

#### **FEATURES**

- Designed to maintain appearance push after push
- Moving parts are accessible behind actuator flush plate
- · Made of glass, zinc die cast and plated
- Available in a variety of unique combinations of finish/color
- Incorporates water saving possibilities when used with Geberit dual-flush tanks
  1.6 GPF (6 LPF) and 0.8 GPF (3 LPF) or
  1.28 GPF (4.8 LPF) and 0.8 GPF (3 LPF)
- Includes mounting frame and hardware
- Optional cover frame available as needed to cover rough edges or imperfect wall openings.

#### WARRANTY


• One-year limited warranty.

## Dual-Flush Actuators, Omega 2x6 Installation


Style	Material	Finish	Model No.
Omega60	Zinc	Brushed Chrome	115.081.GH.1
	Glass	Lava Glass <b>NEW!</b>	115.081.JK.1
		Grey Sand Glass <b>NEW!</b>	115.081.JL.1
		White Glass-Aluminum	115.081.Sl.1
		Black Glass-Aluminum	115.081.SJ.1
	Zinc	Cover frame (when needed) Brushed Chrome	115.086.GH.1
		Cover frame (when needed) Polished Chrome	115.086.21.1

### **DIMENSIONS**

#### Omega60 Dual-Flush



#### **Omega60 Cover Frame**



Products marked with comply with the American Disabilities Act (ADA) when installed per the requirements of the latest ADA Accessibility Guidelines (ADAAG) and/or ICC/ANSI A117.1.



ARCHITECT/ENGINEER APPROVAL				
Job Name:				
Date:	Quantity:			
Model Specifi	ed:			
Variations Spe	ecified:			
Customer/Wh	olesaler:			
Contractor:				
Architect:				



Geberit 2100 S. Clearwater Drive Des Plaines, IL 60018 USA

P 847-803-7777 F 847-849-1845

www.geberit.us